



UL 标准 UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/15	/	/
螺丝扭矩/Torque Tightening(N·m/Lb.in)	M3: 0.5/4.43		
线径范围(硬线和软线)/Wire Range(Rigid and flexible)(AWG/mm²)	22~14		
间距/Pitch(mm)/线数范围/Poles	7.62/N=02~24P		
使用温度范围/Operating temperature(°C)	-40~+105		
符合 RoHS 环保要求/Conform to RoHS	Yes		

MATERIAL: SURFACE: SA25R-7.62

MAT NO.:
STATUS:
APPD:
CHKD:
DRT:

NAME: 宁波三安电子科技有限公司
Sanan Electrical Technology Co. Ltd

DRAWING NO.: SA25R-7.62-XXP-1Y-00A(H)
TYPE: SCALE: SHEET 1/1

公差/General	公差/ tolerances(mm)
0	>3
~	>6
~	>10
~	>18
~	>30
~	>50
~	>80
~	>120
~	>180
~	>250
~	>315
~	>400
~	>500
±Z'	

公差/General	公差/ tolerances(mm)
0	>3
~	>6
~	>10
~	>18
~	>30
~	>50
~	>80
~	>120
~	>180
~	>250
~	>315
~	>400
~	>500
±Z'	