



3	Screw cap	Copper alloy	/
2	Pin	Copper alloy	Sn plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准 /UL Standard:	B	C	D
额定电压/电流 / Rated Voltage(V)/Current(A)	300/8	/	300/8
IEC 标准 /IEC Standard:	/	/	/
过压类别 /Overvoltage Category /污染等级 / Pollution Degree	III/3	III/2	II/2
额定电压/电流 / Rated Voltage(V)/Current(A)	/	/	250/7
额定脉冲电压 (KV) /Rate Impulse Voltage (KV)	/	/	2.5
间距 /Pitch(mm) /线数范围 /Poles	3.50/N=02~22P		
使用温度范围 /Operating temperature(°C)	-40~+105		
符合RoHS环保要求 /Conform to RoHS	Yes		

MATERIAL: SURFACE:

MAT NO.:
STATUS:
APPD:
CHKD:
DRT:

NAME: 15ESARM-3.5-XXP-1Y-00A(H)
DRAWING NO.:

SIZE: A4
SCALE: 1/1

公差 (General tolerances)(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

0.1/10
±2°



宁波三安电子科技有限公司
Sanan Electrical Technology Co., Ltd